OAKFIELD STONE COMPANY
920 - 922 - 8744
Oakfield, Wisconsin

OAKFIELD STONEGATE

SPECIFICATIONS

THIN VENEER ☑ FULL VENEER ☑ bimobject ☑

ORIGIN	OAKFIELD, WISCONSIN
INFO	100% SPLITFACE, MACHINE CUT
PATTERN	NATURAL, RANDOM ASHLAR
COLOR	GRAY / BEIGE WITH GOLDS, TANS, AND EARTHY TONES
AREA	40 SQFT / TON (FULL) 12-15 LBS/SQFT (THIN)
HEIGHT	RANDOM 2" - 6"
LENGTH	6" - 24" THIN VENEER CORNERS: 6"-13"
WIDTH	FULL: 3"-5" (4") THIN: 3/4"- 1-1/2"
DENSITY	176 LB/FT3

ASTM – C170 COMPRESSIVE STRENGTH

24,740 PSI	PERPENDICULAR TO RIFT, WET
31,490 PSI	PERPENDICULAR TO RIFT, DRY
27,060 PSI	PARALLEL TO RIFT, WET
25,060 PSI	PARALLEL TO RIFT, DRY

ASTM – C97 ABSORPTION & SPECIFIC GRAVITY

.29%	WATER ABSORPTION
2.81	BULK SPECIFIC GRAVITY

ASTM – C880 FLEXURAL STRENGTH

1,010 PSI	AVERAGE FLEXURAL STRENGTH, WET
1,020 PSI	AVERAGE FLEXURAL STRENGTH, DRY

NATURAL STONE INSTITUTE